

GV-VD8700 8MP H.265 Low Lux WDR IR Vandal Proof IP Dome




- Sensore CMOS progressivo low lux da 1/2,5 pollici
- Illuminazione minima a 0,04 lux
- Triple stream da H.265 e H.264
- Fino a 30 fps a 3840 x 2160
- Resistenza al vandalismo (IK10)
- Protezione da ingressi (IP66)
- Obiettivo varifocale megapixel
- Obiettivo P-iris per il controllo automatico dell'iride
- Funzione giorno e notte (con filtro IR-cut rimovibile)
- IR intelligente
- Ampia gamma dinamica (WDR)
- Distanza IR fino a 40 m (130 ft)
- Meccanismo a 3 assi (pan / tilt / rotazione)
- Un ingresso per sensore e un'uscita digitale
- Slot per scheda micro SD integrato (SD/SDHC/SDXC/UHS-I, Classe 10) per archiviazione locale
- DC 12V / PoE (IEEE 802.3af)
- Audio unidirezionale
- Defog (anti-appannamento)
- Rilevamento del movimento
- Allarme di manomissione
- Riconoscimento facciale
- Sovrapposizione di testo
- Maschera di privacy
- Filtraggio degli indirizzi IP
- Registrazione assegnata da GV-Edge Recording Manager (Windows & Mac)
- Supporta iPhone, iPad e Android
- 4 lingue nell'interfaccia web

Introduzione

La telecamera Dome IP antivandalismo GV-VD8700 dispone di tecnologia all'avanguardia per il riconoscimento facciale, che consente agli utenti di identificare in tempo reale il personale importante presente nel suo database. La telecamera può gestire fino a 10.000 profili facciali nel suo database, categorizzabili per rispondere a diverse necessità aziendali, come il miglioramento del servizio clienti, la gestione della sicurezza e altro. Il sistema di riconoscimento facciale della telecamera è efficace fino a una distanza di 4 metri (circa 14 piedi) e può identificare fino a 10 persone contemporaneamente. Con un tempo di riconoscimento inferiore ai 2 secondi, la telecamera è in grado di identificare rapidamente ospiti VIP e/o potenziali intrusi. Quando integrata con il software GV-VMS, il riconoscimento facciale della GV-VD8700 può essere utilizzato per innescare allarmi in base a regole predefinite, garantendo così una gestione della sicurezza più efficace e affidabile.

Come telecamera da esterno, la GV-VD8700 è stata progettata per resistere agli atti vandalici con una classificazione IK10 e per proteggersi contro le infiltrazioni con una classificazione IP66. La telecamera supporta il codec video H.265, che permette di ottenere un migliore rapporto di compressione mantenendo al contempo immagini di alta qualità con minori larghezze di banda di rete. Per le operazioni notturne, la telecamera è dotata di una distanza efficace degli IR fino a 40 metri (circa 130 piedi). Le sue funzionalità di WDR (Wide Dynamic Range) e compensazione del controllo consentono alla telecamera di rilevare i volti anche in ambienti con forti contrasti di luce.

Riconoscimento facciale in tempo reale su visualizzazione dal vivo



Eventi facciali recuperabili

SettingLicenseManagementEvents

2018/02/10 21:47:50 ~ 2018/02/11 21:47:50 Query ☐ Auto Polling 10 ☐ Advance Search

Show 10 entries

Timestamp	Name	Image	Conf0	Conf1	Conf2
Sunday, February 11, 2018 10:44:55	Unknown		Mark_Lin 51	Peter_Liu 44.2	Ray_Su 43.2
Sunday, February 11, 2018 10:35:50	Cathy Lee		Cathy_Lee 57.3	Zach_Lin 48.9	Kylin_Lin 44.3
Sunday, February 11, 2018 10:48:35	Hunter Roberts		Hunter_Roberts 55.9	Peter_Liu 54.6	Ray_Su 49.9
Sunday, February 11, 2018 10:47:57	Anna Wilson		Anna Wilson 57.3	Daniel_Chung 42.4	Mars_Lin 40.4
Sunday, February 11, 2018 10:49:51	Bonnie Brown		Bonnie Brown 64.9	Mark_Lin 48.3	Kim_Lu 41.7
Sunday, February 11, 2018 10:49:43	Dylan Thomas		Dylan Thomas 58.5	Cesar_Liu 40.6	York_Yang 37.8

Active Tampering Alarm


Tampered






Focus Change



Camera Shift



Dimensioni



Specifiche

Camera		
Image Sensor		1/2.5" progressive scan low lux CMOS
Picture Elements		3840 (H) x 2160 (V)
Minimum Illumination	Color	0.05 Lux
	B/W	0.04 Lux
	IR ON	0 Lux
Shutter Speed		Automatic, Manual (1/30 ~ 1/8000 sec.)
White Balance		Automatic, Manual (2800K ~ 8500K)
Gain Control		Automatic
S/N Ratio		56 dB
WDR		Yes
Dynamic Range		96 dB
Lens		
Megapixel		Yes
Day/Night		Yes (with removable IR-cut filter)
Focal Length		3.3 ~ 12 mm
Lens Type		Varifocal
Maximum Aperture		F/1.4
Mount		Ø14 mm
Horizontal FOV		106° ~ 42°
Image Format		1/2.5"
Operation	Focus	Manual (with lock)
	Zoom	Manual (with lock)
	Iris	P-iris
IR LED Quantity		20 IR LEDs
Max. IR Distance		40 m (130 ft)
Face Recognition		
Environment		600 lux
Recognition face angle	Tilt (Up/Down)	± 15°
	Swing (Left/Right)	± 15°
Max. No of Faces		Up to 10
Min. face image pixel requirement		120 x 120

Operation		
Video Compression		H.265, H.264
Video Streaming		Stream 1 from H.265 or H.264 Stream 2 from H.264 Stream 3 from H.264
Frame Rate		30 fps at 3840 x 2160 (50 / 60 Hz) * The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
Image Setting		Brightness, Contrast, Saturation, Sharpness, White Balance, Flicker-less, Image Orientation (Flip, Mirror, 0°, 180°), Shutter Speed, D/N Sensitivity, Backlight Compensation, WDR, Defog
Video Analytics		Motion Detection, Tampering Alarm, Face Detection, Face Recognition
Audio Compression		G.711
Audio Support		One-way audio
Sensor Input		1 input (Dry contact)
Alarm Output		1 digital output (200 mA 5V DC)
Intelligent Video		
Video Analytics		Motion Detection, Tampering Alarm, Face Detection, Face Recognition
Video Resolution		
Main Stream	4:3	2560 x 1920, 2048 x 1536, 1600 x 1200, 1280 x 960
	16:9	3840 x 2160 (Default), 2560 x 1440, 1920 x 1080, 1280 x 720
Sub Stream	4:3	1024 x 768, 640 x 480, 320 x 240
	16:9	1280 x 720, 640 x 360 (Default)
Third Stream	4:3	640 x 480, 320 x 240
	16:9	640 x 360 (Default)
Network		
Interface		10/100 Ethernet
Ethernet Protocol		DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, RTSP, SMTP, TCP, UDP
Mechanical		
Temperature Detector		Yes
Camera Angle Adjustment	Pan	0° ~ 350°
	Tilt	0° ~ 75°
	Rotate	0° ~ 340°
Connectors	Power	2-pin terminal block (DC 12V, 3A), PoE
	Ethernet	Ethernet (10/100 Base-T), RJ-45
	Audio	1 In (built-in or 3.5 mm phone jack for external microphone with power supply) 1 Out (3.5 mm phone jack for speaker) (Currently not functional)
	Digital I/O	I/O wires
	Local Storage	Micro SD card slot (SD/SDHC/SDXC/UHS-I, Class 10) *UHS-II card type is not supported.
LED Indicator		2 LEDs: Power, Status
General		
Environment Temperature	Start-up	-20 °C ~ 50 °C (-4 °F ~ 122 °F)
	Operation	-30 °C ~ 50 °C (-22 °F ~ 122 °F)
Humidity		10% ~ 90% (no condensation)
Power Source		12V DC / PoE (IEEE 802.3af)
Max. Power Consumption		11.04 W
Dimension		Ø 160 x 108.4 mm (6.2 x 4.27")
Weight		1.2 kg (2.64 lb)
Ingress Protection		IP66
Vandal Resistance		IK10
Regulatory		CE, FCC, RCM, LVD, RoHS compliant
Power over Ethernet		
PoE Standard		PoE (IEEE 802.3af Power over Ethernet / PD)
PoE Power Supply Type		End-Span and Mid-Span
PoE Power Output		Per Port 48V DC, 350 mA. Max. 15.4 watts

Web Interface	
Installation Management	Web-based configuration
Maintenance	Firmware upgrade through Web Browser or Utility
Access from Web Browser	Camera Live View, Video Recording, Change Video Quality, Bandwidth Control, Image Snapshot, Audio, Picture in Picture, Privacy Mask, Text Overlay
Language	English / Japanese / Simplified Chinese / Traditional Chinese
Applications	
Software Supported	GV-DVR / NVR (V8.7.4.0), GV-VMS (V17.1), GV-Control Center (V3.5.0.0), GV-Edge Recording Manager (V1.3.0.0), GV-Recording Server / Video Gateway (V1.3.0.0) *GV-VMS V17.1 supports Face Detection, Face Recognition and Live View. Other GV-Software only supports Live View.
Smart Device Access	GV-Eye for iOS and Android
Live Viewing	Web browser, Mobile app

Note: Specifications are subject to change without prior notice.


Packing List

- | | |
|--|---|
| 1. H.265 Vandal Proof Dome | 11. Torx Wrench |
| 2. Screw x 4 | 12. Big Concave Hexagon Wrench |
| 3. Screw Anchor x 4 | 13. Small Concave Hexagon Wrench |
| 4. Audio Wires x 2 | 14. Silica Gel Bag |
| 5. I/O Cable | 15. Sticker (for Silica Gel Bag) |
| 6. Installation Sticker | 16. Ruler |
| 7. Conduit Converter | 17. 8 GB Micro SD Card (MLC, SDHC, Class 10) |
| 8. PG21 Conduit Connector | (The Micro SD Card is preinstalled and formatted in the camera) |
| 9. RJ-45 Connector | 18. Download Guide |
| 10. Waterproof Rubber Sets | 19. Warranty Card |
| (for RJ-45 Cat.5 and DC 12V / for RJ-45 Cat.6) | |

Note: Power adapters can be purchased upon request.

Accessories

Model No.	Name		Details
GV-Mount100	Straight Tube and Junction Box Kit		Dimensions: 200 x 170 x 257.5 mm (7.9 x 6.7 x 10.1") Weight: 3.17 kg (6.99 lb)
GV-Mount101	Straight Tube Kit		Dimensions: 219 x 125 x 332 mm (8.6 x 4.9 x 13.1") Weight: 1.8 kg (3.97 lb)
GV-Mount200	Wall Pendant Mount		Dimensions: 225 x 140 x 250 mm (8.9 x 5.5 x 9.8") Weight: 900 g (1.98 lb)

GV-Mount203	Wall Mount and Junction Box		Dimensions: 315 x 195.5 x 225 mm (12.4 x 7.7 x 8.9") Weight: 2.95 kg (6.5 lb)
GV-Mount206	Wall Box Mount		Dimensions: 126.5 x 211.3 x 176.85 mm (5 x 8.3 x 6.96") Weight: 0.93 kg (2.06 lb)
GV-Mount300-1	Convex Corner Adapter Kit		Dimensions: 238.6 x 409.5 mm (9.4 x 16.1") Weight: 4.27 kg (9.41 lb)
GV-Mount310-1	Concave Corner Adapter Kit		Dimensions: 123.3 x 393.1 mm (4.9 x 15.5") Weight: 2.96 kg (6.53 lb)
GV-Mount400-1	Pole Mount Bracket Kit (Ø 4 ~ 6")		Bracket: 241 x 161 mm (9.5 x 6.3") Weight: 1.70 kg (3.75 lb) Steel Strap Diameter: Ø 101 ~ 152 mm (4 ~ 6")
GV-Mount410-1	Pole Mount Bracket Kit (Ø 6 ~ 7.5")		Bracket: 241 x 161 mm (9.5 x 6.3") Weight: 1.70 kg (3.75 lb) Steel Strap Diameter: Ø 152 ~ 191 mm (6 ~ 7.5")
GV-Mount702	Extension Tube		Four options are available. Dimensions: Ø 5.4 x 10 or 20 or 30 or 50 cm (Ø 2.1 x 3.9 or 7.9 or 11.8 or 19.7") Weight: 180 g or 390 g or 550 g or 800 g (0.4 lb or 0.86 lb or 1.21lb or 1.76 lb)
GV-Mount903-1	Dome Housing		Dimensions: Ø 185.51 x 165.35 mm (Ø 7.3" x 6.51") Weight: 900 g (1.98 lb)
GV-Mount916	In-Ceiling Mount		Dimensions: Ø 205 x 63.8 mm (Ø 8 x 2.5") Weight: 645 g (1.42 lb)

GV-PA191

PoE Adapter



The GV-PA191 is a Power over Ethernet (PoE) adapter designed to provide power to the IP device through a single Ethernet cable.

GV-PoE Switch

The GV-PoE Switch is designed to provide power along with network connection for IP devices. The GV-PoE Switch is available in various models with different numbers and types of ports.

GV-FWC

GV-FWC can integrate GV-Face Recognition Cameras and GV-AI FR into access control systems by sending access card data, paired to Face IDs, to controllers either through TCP/IP or Wiegand connection.

GV-Relay V2



The GV-Relay V2 is designed to expand the voltage load of GV IP devices. It provides 4 relay outputs, and each can be set as normally open (NO) or normally closed (NC) independently as per your requirement.

Metal PG21 Conduit Connector



The metal PG21 conduit connector allows you to run the wires through a 3/4" conduit pipe.

Power Adapter

Contact our sales representatives for the countries and areas supported.