

GF1922 GF Fingerprint Reader



The fingerprint reader, when combined with the GeoVision controller and access control system GV-ASManager, can be used to create a comprehensive access control system. Three modes of operation are possible: cards with fingerprints, fingerprints alone, and cards only.

Key Features

- Three types of access modes: cards only, fingerprints only, and cards with fingerprints
- Store fingerprint templates on the user card (Card with Fingerprint Mode)
- Fingerprint enrollment with GV-ASManager (Fingerprint Only Mode)
- GeoVision access cards with GID (GeoVision Identifier) support
- Optical sensor
- Standalone mode available

Specifications

Hardware		
Application		Indoor use only
Sensor		Optical
Sensing Area (H x W)		20 x 17 mm (0.79 x 0.67 in)
Output Interface		DC 30 V, 0.3A
Input Interface		2 Ports, dry-contact
Communication Interface		TCP/IP (LAN / WAN)
Frequency		13.56 MHz ISO 14443A
Function		
Operation Mode		Fingerprint Only, Card + Fingerprint, Card Only
Fingerprint Enrollment	(Fingerprint Only Mode)	TCP/IP
	(Fingerprint + Card Mode)	
Firmware Upgrade		TCP/IP
Number of Fingerprints Stored		1,900 (for Fingerprint Only mode)
Standalone Function		Yes (for Fingerprint Only mode)
General		
Operating Temperature		0 ~ 50° C (32 ~ 122° F)
Humidity		10% ~ 90% (no condensation)
Power		DC 7 ~ 15 V, Max 250mA
Dimensions (H x W x D)		138 x 59 x 48 mm (5.43 x 2.32 x 1.89 in)
Weight		160 g (0.35 lb)
Certification		CE, FCC

Note:

- For data synchronization with GV-AS Controller and GV-ASManager via Ethernet, it only supports the following controller firmware and software versions:
 - GV-ASManager: V4.0 or later
 - GV-AS1010 and GV-EV48: V1.0 or later
 - GV-AS1620 V1.00 or later
 - GV-AS2120 V1.41 or later
 - GV-AS4110 / 8110: V1.23 or later
 - GV-CS1320 V2.00 or later
- GV-GF1922 do not support third-party controllers.
- All specifications are subject to change without prior notice.

Options

GV-AS ID Card, Key Fob, Sticker	GV-AS ID Cards, Key Fobs and Stickers are available for Card + Fingerprint Mode or Card Only Mode
---------------------------------	---

Packing List

- Fingerprint reader
- Data Cable (of 30 cm / 0.98 feet)
- Manager Enroll Card
- Manager Delete Card
- Mounting Plate
- Standard Screw x 2
- Plastic Screw Anchor x 2
- Security Screw
- Torx Wrench
- Connector Wire
- Software CD
- Warranty Card