

GV-POE0400-V2 4-Port 802.3af/at PoE Switch



- 5-port 10/100BaseTX, 4-port with PSE/Power over Ethernet
- IEEE 802.3af/at Compliant
- Max. 60 W PoE Budget
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- 5" Metal Case of Palm Size
- Up to 4 GV-IP Cameras support

Introduzione

GV-POE0400-V2 è uno switch Desktop PoE Fast Ethernet a 5 porte 10/100Base-TX, dotato di 4 porte PSE/PoE. Lo switch supporta lo standard IEEE 802.3af/at Power over Ethernet, fornendo fino a 30 W per porta e un PoE Budget massimo di 60 W.

Elimina la necessità di utilizzare cavi di alimentazione dedicati per collegare dispositivi alimentati (PD), come le telecamere IP.

È la soluzione ideale per piccoli ambienti di rete che necessitano di una connessione più stabile ed efficiente

Specifiche

Ethernet	
Layer Supported	L2
Ports	
Number of Ports	5 ports (Fast Ethernet 10/100BaseTX, 4 ports with IEEE 802.3at PSE)
Performance	
MAC Address	1 K
Buffer Memory	384 K bits
Transmission Method	Store and Forward
Transmission Media	10BaseT Cat. 5 UTP/STP 100BaseTX Cat. 5 UTP/STP
Filtering/Forwarding Rates	10 Mbps port - 14,880 pps 100 Mbps port - 148,800 pps
Backplane Capacity	1 Gbps
Power over Ethernet	
PoE Standard	IEEE 802.3af/at compliant
PoE Max Power per Port	30 W
PoE Power Budget	60 W
PoE Mode	Mode B
Mechanical	
LED Indicators	Per Port: Link/Act PoE Act/Status Power
General	
Dimensions (H x W x D)	24 x 130 x 98 mm (0.94" x 5.11" x 3.86")
Weight	0.76 kg (1.68 lb)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 90°C (-4°F ~ 194°F)
Humidity	10 to 90% RH (non-condensing)

Power Requirements

Power Input	100 ~ 240 V/AC, 50 ~ 60 Hz
Max Power Consumption	65 W (ADP with Level VI certificated)

Standards and Regulatory

Standards	IEEE-802.3at PoE+ / PSE IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow Control
Certification	CE, FCC Class A, RoHS compliant

Note: Specifications are subject to change without notice.

Packing List

1. GV-POE0400-V2
2. AC Power Cord
3. Power Adapter
4. Download Guide
5. GV-POE0400-V2 Installation Guide

Front View



Rear View



Dimensions

