

GV-PA301 Gigabit PoE Adapter



Introduction

GV-PA301 is a Gigabit Power over Ethernet (PoE) adapter. It fully complies with IEEE 802.3 af/at standard. It can work with all IEEE 802.af/at PoE compliant PD (Powered Device) and PSE (Power Sourcing Equipment) or other equivalent products with a maximum power output of 15.4 W / 30 W over a single Ethernet cable. Adopting the PoE adapter enables you to mount an IP device anywhere in a building where power outlets are not available.

Specifications

Model	GV-PA301
PoE Standard	Power over Ethernet (IEEE 802.3af/at, Max. 15.4 W / 30 W)
Speed	10/100/1000 Mbps
PoE Output	DC 55 V (Max. 30W)
Ethernet Cable Length	Max. 100 m (328 ft) from Switch to IP device, CAT5/5e/6
Power Input	AC 100 ~ 240 V, 50/60 Hz
Operation Temperature	0 °C ~ 40 °C (32°F ~ 104°F)
Dimensions (L x W x H)	116 x 60 x 33 mm (4.57" x 2.36" x 1.3")
Weight	400 g (0.88 lb)
PoE Power Supply Type	Data Pairs (1, 2 + / 3, 6 -)
Surge protection	Differential mode ±1 kV; Common mode ±2 kV
Certification	CE / FCC / UKCA / RCM / RoHS compliant
Compatible GV-IP Device	General GV-IP cameras with PoE support and a power consumption of less than or equal to 30 W

Note: Specifications are subject to change without notice.

Packing List

1. GV-PA301 PoE adapter x 1
2. Power Cord x 1