

GV-PA902BT Gigabit BT PoE++ Adapter



Introduction

GV-PA902BT is a Gigabit PoE (Power over Ethernet) adapter. The adapter supports IEEE802.3af/at/bt Power over Ethernet standard, and can output up to 95 W over a single Ethernet cable. The PoE adapter allows you to place an IP camera anywhere in a facility where power outlets are limited.

Specifications

Port	Data in port: 1 x 10/100/1000 Mbps RJ-45 port PoE out port: 1 x 10/100/1000 Mbps RJ-45 port
Power Source	High Power Over Ethernet (Max. 95 W)
PoE Power Output	DC 54V (Max. 95 W)
Ethernet Cable Length	Max 100 m (328 ft) from GV-PA902BT to IP device, CAT5e, 6
Power Input	AC 100V ~ 240V, 50/60 Hz
Operation Temperature	Operating Temperature: 0°C ~ 40 °C (32 °F ~104°F) Storage Temperature: -40 °C ~ 70 °C (-40 °F ~158°F)
Humidity	Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
Surge Protection	±6 kV
Dimensions (L x W x H)	170 x 102 x 40 mm (6.69" x 4.01" x 1.57")
Weight	0.95 kg (2.09 lb)
Standard	IEEE802.3af/at/bt
Energy Efficiency Grade	6

Note: The specifications are subject to change without notice.

Packing List

- GV-PA902BT x 1
- Power Cord x 1
- Rubber Feet x 4

Compatible GV-IP Devices

- GV-LPR2800-DL
- GV-PPTZ7300 / 14021 / 14031
- GV-QSD5731-IR
- GV-SD2301 V2 / 2411 V2 / 2723-IR / 2733-IR
- GV-SV48000

Dimensions

